









Tabella di adattabilità per profili italiani / Suitability table for italian profile

1341	1341.2
      	
<p>Euro Keeper 45</p> <p>Keeper 53/60</p> <p>Keeper 61/68</p> <p>All.co 5/TT sorm.</p> <p>Alsec 2000 (59/69)-2000/120</p> <p>Alsec IS 55</p> <p>Alusuisse AS 46</p> <p>BGA 50/BT 60 TT</p> <p>Domal Break PA 52/62/70</p> <p>Domal Stopper 38/45 e 45/52</p> <p>Domal Stopper PG</p> <p>Domal Stopper PG compl. int.</p> <p>Ekip 40/ev sorm.</p> <p>Ekip 60 TT</p> <p>Eku 53</p> <p>Eku 64 TT/72 TT</p> <p>Esedra 53/75 TT</p> <p>Euro 40 compl./sorm.</p> <p>Eurotherm 54 sorm.</p> <p>Export 40/45 TT/50/50 TT</p> <p>FC 47compl./sorm.</p> <p>FC 55 Bicolore/Restauro</p> <p>FC 55 Montecarlo compl.</p> <p>FC 60 TT Polo compl.</p> <p>FC 62 TT compl./sorm.</p>	<p>All.co 5/TT sorm.</p> <p>Ekip 40/ev. sorm.</p> <p>New Tec 50/52 TT/60 TT</p> <p>New Tec 68 Super Thermic</p> <p>R 40</p>
<p>Per profili con cava mm:</p> <p>10x14,3</p> <p>12x15</p> <p>12,5x16,5</p> <p>13,5x16,5</p> <p>14x18</p>	<p>Global 41-Global 48</p> <p>Gold 400/490 TT/500/600 TT</p> <p>NC 45 Int./Int.com.int./S.Thermic</p> <p>NC 55 Int./Th.</p> <p>NC 68 S. Th.</p> <p>Nuovo NC 40/50 sorm.</p> <p>Riviera/TT</p> <p>Sistema 1 compl.est./sorm.</p> <p>SV 47/55-SV 55 TT/70 TT</p> <p>Syntesis 45/57/TT</p>